



# UPVC Paint

## Description

H+G uPVC Paint is an incredibly tough and durable interior and exterior paint for uPVC window frames, doors and cladding, with a lustrous, velvety finish. Surfaces are easily washed and have high scrub and mould growth resistance. What's more, no primer or undercoat is required.

## TYPICAL USES

High use interior trim surfaces, doors, hand rails etc where regular hand contact occurs.  
Metal radiators and surfaces (with appropriate metal primer on bare steel substrates)

## PHYSICAL PROPERTIES

Sheen level\* – approximately 20%  
Coverage – up to 17 square metres per litre per coat (varies with substrate and texture)  
Recommended number of coats – 2 (some strong colours may require an extra coat)  
Touch dry and re-coat time – approximately 20 minutes and 1 hour (dependant on atmospheric conditions).  
Volume solids – approximately 42%  
Colour availability – any colour  
Pack sizes – 2.5, 5 litres  
Odour – virtually nil  
\*Final sheen level is given based upon two full coats being applied

## ENVIRONMENT

2010 maximum permitted limit grams per litre – 140g/l  
VOC category for this product – A(i)  
Actual VOC content grams per litre – Approx. 25 g/l  
Classification – low

## HEALTH & SAFETY

Our products are designed to cause no harm when used as directed. Safety information can be found on the pack with more detailed safety information available on our website or on request.

## SURFACE PREPARATION

Ensure that surfaces are free from dirt, dust, grease, mould and any other contaminants that may affect adhesion. Clean off any surface mould and algae with a fungicidal cleaner and rinse off. Contaminated areas should be washed down thoroughly with sugar soap and rinsed off. Previously painted surfaces should be lightly sanded and then cleaned with a lint free cloth. Imperfections and loose flaking paint should be sanded to remove as required, and all dry previously painted edges feathered off to a smooth finish. No undercoat or primer is required when correct preparation has been completed.

## APPLICATION

This product can be applied in temperatures between 5°C and 30°C. Avoid application in direct sunlight. Take care to avoid contact with the painted surface before the product has been able to fully dry. Always follow the touch dry and re-coat times stated above. Brushing - Use only high quality synthetic brushes suitably sized for the job in hand. Ensure that brushes are sufficiently dry after washing out before use. Apply paint generously with even brush strokes maintaining a wet edge as you progress leaving the paint to find its own level. Do not overwork and take care not to brush over paint that has already started to dry.





# UPVC Paint

Roller - Use only short napped synthetic rollers for the best result on larger areas. Take care to maintain a wet edge and to avoid lapping marks and flashing. Never over roller paint that has started to dry.

Spray application - For airless spray application, dilute paint by up to 25%. Use tip sizes and pressure based upon the job in hand. In all instances, seek technical guidance from the manufacturers of the spray equipment.

---

## CLEAN UP & DISPOSAL

Remove excess paint from all equipment. The cleaning of brushes and rollers should be carried out immediately using clean water. Cleaning is most effective if the water is slightly warm.

---

## STORAGE & SHELF LIFE

To avoid risk of spillage, always store and transport in a secure upright position. Storage of paint should be in a cool dry and frost-free environment, away from direct heat and sunlight. Products that are unopened can be stored at least two years and containers which are opened must be free of contaminants and should be properly resealed and kept upright. All products will need to be stirred thoroughly.

---

## LIFE CYCLE MAINTENANCE

Cleaning - Surfaces should be washed down with dilute detergent solution when required to remove build-up of dirt or grime. This is especially important on horizontal exterior areas such as sills where algae can eventually grow on accumulated dirt.

Disclaimer - The information in this product information sheet is correct to the best of our knowledge and experience. Hanford + Green reserves the right to modify data contained herein, without notice.

The information supplied does not absolve users from responsibility to carry out their own tests and experiments, nor does it imply any legally binding assurance of certain properties or suitability for any specific purpose. Conditions of service may be beyond our control, so no liability whatsoever can be accepted on the basis of the information supplied herein.